

HKD®

ELECTRIC HOIST & WINCH



MORE POWERFUL



CONTENTS



P.05

HKD Grooved Winch
HKD Portable Crane With Grooved Winch

P.06

HKD Suspension Grooved Winch
HKD Electrical Monorail Grooved Winch

P.07

HKD Monorail Grooved Winch With Plain Trolley
HKD Monorail Grooved Winch With Gear Trolley

P.08

HKD Mini Winch
HKD Monorail Mini Winch With Plain Trolley
HKD Monorail Mini Winch With Gear Trolley



HKD PORTABLE CRANE WITH DRUM WINCH VOLTAGE : SINGLE PHASE 220V 50HZ

Model	Capacity (kg)	Speed (m/min)	Lifting Height (meter)	Wire Rope (mm/m)	Motor (kw)	Duty Rating (%)
HKD-30-202S	200	15 ~ 18	28	6 x 30	0.5	25
HKD-30-204S	250	15 ~ 18	28	7 x 30	1.1	
HKD-30-208S	350	15 ~ 18	28	7 x 30	1.1	
HKD-30-210S	500	21 ~ 25	42	8 x 45	1.5	
HKD-30-210SL		21 ~ 25	95	8 x 100	1.5	
HKD-30-210SXL		21 ~ 25	195	8 x 200	1.5	



HKD-30-202 S

HKD PORTABLE CRANE WITH DRUM WINCH VOLTAGE : 3 PHASE 415V 50HZ

Model	Capacity (kg)	Speed (m/min)	Lifting Height (meter)	Wire Rope (mm/m)	Motor (kw)	Duty Rating (%)
HKD-30-202	200	15 ~ 18	28	6 x 30	0.5	45
HKD-30-204	250	15 ~ 18	28	7 x 30	1.1	
HKD-30-208	350	15 ~ 18	28	7 x 30	1.1	
HKD-30-210	500	21 ~ 25	42	8 x 45	1.5	
HKD-30-210L		21 ~ 25	95	8 x 100	1.5	
HKD-30-210XL		21 ~ 25	195	8 x 200	1.5	

HKD SUSPENSION DRUM WINCH VOLTAGE : SINGLE PHASE 220V 50HZ

Model	Capacity (kg)	Speed (m/min)	Lifting Height (meter)	Wire Rope (mm/m)	Motor (kw)	Duty Rating (%)
HKD-40-202S	200	15 ~ 18	28	6 x 30	0.5	25
HKD-40-204S	250	15 ~ 18	28	7 x 30	1.1	
HKD-40-208S	350	15 ~ 18	28	7 x 30	1.1	
HKD-40-210S	500	21 ~ 25	42	8 x 45	1.5	
HKD-40-210SL		21 ~ 25	95	8 x 100	1.5	
HKD-40-210SXL		21 ~ 25	195	8 x 200	1.5	



HKD-40-202 S

HKD SUSPENSION DRUM WINCH VOLTAGE : 3 PHASE 415V 50HZ

Model	Capacity (kg)	Speed (m/min)	Lifting Height (meter)	Wire Rope (mm/m)	Motor (kw)	Duty Rating (%)
HKD-40-202	200	15 ~ 18	28	6 x 30	0.5	45
HKD-40-204	250	15 ~ 18	28	7 x 30	1.1	
HKD-40-208	350	15 ~ 18	28	7 x 30	1.1	
HKD-40-210	500	21 ~ 25	42	8 x 45	1.5	
HKD-40-210L		21 ~ 25	95	8 x 100	1.5	
HKD-40-210XL		21 ~ 25	195	8 x 200	1.5	



HKD-40-202



**HKD ELECTRICAL MONORAIL DRUM WINCH C/W WIRELESS REMOTE CONTROL
VOLTAGE : SINGLE PHASE 220V 50HZ**

Model	Capacity (kg)	Speed (m/min)	Lifting Height (meter)	Wire Rope (mm/m)	Motor (kw)	Trolley Speed (m/min)	Trolley Motor (kw)	Flange Width (mm)	Duty Rating (%)
HKD-50-202S	200	15 ~ 18	28	6 x 30	0.5	14	0.4	75 ~ 200	25
HKD-50-204S	250	15 ~ 18	28	7 x 30	1.1	14	0.4	75 ~ 200	
HKD-50-208S	350	15 ~ 18	28	7 x 30	1.1	14	0.4	75 ~ 200	
HKD-50-210S	500	21 ~ 25	42	8 x 45	1.5	14	0.4	75 ~ 200	
HKD-50-210SL		21 ~ 25	95	8 x 100	1.5	14	0.4	75 ~ 200	
HKD-50-210SXL		21 ~ 25	195	8 x 200	1.5	14	0.4	75 ~ 200	

**HKD ELECTRICAL MONORAIL DRUM WINCH C/W WIRELESS REMOTE CONTROL
VOLTAGE : 3 PHASE 415V 50HZ**

Model	Capacity (kg)	Speed (m/min)	Lifting Height (meter)	Wire Rope (mm/m)	Motor (kw)	Trolley Speed (m/min)	Trolley Motor (kw)	Flange Width (mm)	Duty Rating (%)
HKD-50-202	200	15 ~ 18	28	6 x 30	0.5	14	0.4	100 ~ 300	45
HKD-50-204	250	15 ~ 18	28	7 x 30	1.1	14	0.4	100 ~ 300	
HKD-50-208	350	15 ~ 18	28	7 x 30	1.1	14	0.4	100 ~ 300	
HKD-50-210	500	21 ~ 25	42	8 x 45	1.5	14	0.4	100 ~ 300	
HKD-50-210L		21 ~ 25	95	8 x 100	1.5	14	0.4	100 ~ 300	
HKD-50-210XL		21 ~ 25	195	8 x 200	1.5	14	0.4	100 ~ 300	
HKD-50-212	1000	12 ~ 15	42	10 x 45	2.2	14	0.75	100 ~ 300	
HKD-50-212L		12 ~ 15	95	10 x 100	2.2	14	0.75	100 ~ 300	
HKD-50-212XL		12 ~ 15	195	10 x 200	2.2	14	0.75	100 ~ 300	
HKD-50-213	2000	12 ~ 15	42	12 x 45	3.7	14	0.75	100 ~ 300	
HKD-50-213L		12 ~ 15	95	12 x 100	3.7	14	0.75	100 ~ 300	
HKD-50-213XL		12 ~ 15	195	12 x 200	3.7	14	0.75	100 ~ 300	
HKD-50-214	3000	12 ~ 15	42	14 x 45	5.5	14	0.75	100 ~ 300	
HKD-50-214L		12 ~ 15	95	14 x 100	5.5	14	0.75	100 ~ 300	
HKD-50-214XL		12 ~ 15	195	14 x 200	5.5	14	0.75	100 ~ 300	
HKD-50-215	5000	12 ~ 15	42	16 x 45	7.5	14	0.75	100 ~ 300	
HKD-50-215L		12 ~ 15	95	16 x 100	7.5	14	0.75	100 ~ 300	
HKD-50-215XL		12 ~ 15	195	16 x 200	7.5	14	0.75	100 ~ 300	

HKD MONORAIL DRUM WINCH WITH PLAIN TROLLEY VOLTAGE : SINGLE PHASE 220V 50HZ

Model	Capacity (kg)	Speed (m/min)	Lifting Height (meter)	Wire Rope (mm/m)	Motor (kw)	Flange Width (mm)	Duty Rating (%)
HKD-60-202S	200	15 ~ 18	28	6 x 30	0.5	75 ~ 100	25
HKD-60-204S	250	15 ~ 18	28	7 x 30	1.1	75 ~ 100	
HKD-60-208S	350	15 ~ 18	28	7 x 30	1.1	75 ~ 100	
HKD-60-210S	500	21 ~ 25	42	8 x 45	1.5	75 ~ 100	
HKD-60-210SL		21 ~ 25	95	8 x 100	1.5	75 ~ 100	
HKD-60-210SXL		21 ~ 25	195	8 x 200	1.5	75 ~ 100	

HKD MONORAIL DRUM WINCH WITH PLAIN TROLLEY VOLTAGE : 3 PHASE 415V 50HZ

Model	Capacity (kg)	Speed (m/min)	Lifting Height (meter)	Wire Rope (mm/m)	Motor (kw)	Flange Width (mm)	Duty Rating (%)
HKD-60-202	200	15 ~ 18	28	6 x 30	0.5	75 ~ 100	45
HKD-60-204	250	15 ~ 18	28	7 x 30	1.1	75 ~ 100	
HKD-60-208	350	15 ~ 18	28	7 x 30	1.1	75 ~ 100	
HKD-60-210	500	21 ~ 25	42	8 x 45	1.5	75 ~ 100	
HKD-60-210L		21 ~ 25	95	8 x 100	1.5	75 ~ 100	
HKD-60-210XL		21 ~ 25	195	8 x 200	1.5	75 ~ 100	

HKD MONORAIL DRUM WINCH WITH GEAR TROLLEY VOLTAGE : SINGLE PHASE 220V 50HZ

Model	Capacity (kg)	Speed (m/min)	Lifting Height (meter)	Wire Rope (mm/m)	Motor (kw)	Flange Width (mm)	Duty Rating (%)
HKD-70-202S	200	15 ~ 18	28	6 x 30	0.5	75 ~ 100	25
HKD-70-204S	250	15 ~ 18	28	7 x 30	1.1	75 ~ 100	
HKD-70-208S	350	15 ~ 18	28	7 x 30	1.1	75 ~ 100	
HKD-70-210S	500	21 ~ 25	42	8 x 45	1.5	75 ~ 100	
HKD-70-210SL		21 ~ 25	95	8 x 100	1.5	75 ~ 100	
HKD-70-210SXL		21 ~ 25	195	8 x 200	1.5	75 ~ 100	

HKD MONORAIL DRUM WINCH WITH GEAR TROLLEY VOLTAGE : 3 PHASE 415V 50HZ

Model	Capacity (kg)	Speed (m/min)	Lifting Height (meter)	Wire Rope (mm/m)	Motor (kw)	Flange Width (mm)	Duty Rating (%)
HKD-70-202	200	15 ~ 18	28	6 x 30	0.5	75 ~ 100	45
HKD-70-204	250	15 ~ 18	28	7 x 30	1.1	75 ~ 100	
HKD-70-208	350	15 ~ 18	28	7 x 30	1.1	75 ~ 100	
HKD-70-210	500	21 ~ 25	42	8 x 45	1.5	75 ~ 100	
HKD-70-210L		21 ~ 25	95	8 x 100	1.5	75 ~ 100	
HKD-70-210XL		21 ~ 25	195	8 x 200	1.5	75 ~ 100	



HKD-60-202 S



HKD-70-202 S

HKD GROOVED WINCH VOLTAGE : SINGLE PHASE 220V 50HZ

Model	Capacity (kg)	Speed (m/min)	Lifting Height (meter)	Wire Rope (mm/m)	Motor (kw)	Duty Rating (%)
HKD-502S	200	18	28	6 x 30	0.5	25
HKD-504S	250	18	28	7 x 30	1.1	
HKD-508S	350	18	28	7 x 30	1.1	
HKD-510S	500	25	28	8 x 30	1.5	



HKD-502 S

HKD GROOVED WINCH VOLTAGE : 3 PHASE 415V 50HZ

Model	Capacity (kg)	Speed (m/min)	Lifting Height (meter)	Wire Rope (mm/m)	Motor (kw)	Duty Rating (%)
HKD-502	200	18	28	6 x 30	0.5	45
HKD-504	250	18	28	7 x 30	1.1	
HKD-508	350	18	28	7 x 30	1.1	
HKD-510	500	25	28	8 x 30	1.5	
HKD-512	1000	15	42	10 x 45	2.2	
HKD-513	2000	15	42	12 x 45	3.7	
HKD-514	3000	15	42	14 x 45	5.5	
HKD-515	5000	15	42	16 x 45	7.5	

HKD PORTABLE CRANE WITH GROOVED WINCH VOLTAGE : SINGLE PHASE 220V 50HZ

Model	Capacity (kg)	Speed (m/min)	Lifting Height (meter)	Wire Rope (mm/m)	Motor (kw)	Duty Rating (%)
HKD-30-502S	200	18	28	6 x 30	0.5	25
HKD-30-504S	250	18	28	7 x 30	1.1	
HKD-30-508S	350	18	28	7 x 30	1.1	
HKD-30-510S	500	25	28	8 x 30	1.5	



HKD-30-502 S

HKD PORTABLE CRANE WITH GROOVED WINCH VOLTAGE : 3 PHASE 415V 50HZ

Model	Capacity (kg)	Speed (m/min)	Lifting Height (meter)	Wire Rope (mm/m)	Motor (kw)	Duty Rating (%)
HKD-30-502	200	18	28	6 x 30	0.5	45
HKD-30-504	250	18	28	7 x 30	1.1	
HKD-30-508	350	18	28	7 x 30	1.1	
HKD-30-510	500	25	28	8 x 30	1.5	



HKD[®]

